

P6621a

10/079,658

RESPONSE UNDER 37 CFR §1.312

AMENDMENTS TO CLAIMS:

The listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Previously presented) An electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the rotation control unit comprising:

a brake control unit that compares a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

a generator-stop preventing unit that sets the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.

2. (Original) An electronic unit according to Claim 1, wherein the first brake setting value is set to a value that makes the amount of brake applied zero.

3. (Original) An electronic unit according to Claim 1, wherein the first brake setting value is set to a value equal to or less than a minimum amount of brake selected from among a plurality of amounts of brake that can be set in the brake control unit.

4. (Original) An electronic unit according to Claim 1, wherein the generator-stop preventing unit sets the amount of brake applied to the generator to the first brake setting value in synchronization with the rotation period of the generator.

5. (Cancelled)

6. (Previously presented) An electronically controlled mechanical timepiece comprising a mechanical energy source, a generator driven by the mechanical

P6621a

10/079,658

RESPONSE UNDER 37 CFR §1.312

energy source to generate induction electric power to supply electrical energy, a rotation control unit driven by the electrical energy to control the rotation period of the generator, and a time indication unit operated with the rotation of the generator, the rotation control unit comprising:

a brake control unit that compares a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

a generator-stop preventing unit that sets the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.

7. (Previously presented) A control program for an electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the control program for the electronic unit controlling the rotation control unit to:

compare a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

set the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.

8. (Previously presented) A recording medium recording a control program for an electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the recorded control program for the electronic unit controlling the rotation control unit to:

Customer No. 20178
312 Response

3

P6621a

10/079,658

RESPONSE UNDER 37 CFR §1.312

compare a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

set the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.

9. (Previously presented) A control method for an electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the control method comprising:

comparing a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

setting the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.

10. (Currently amended) A method for manufacturing an electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the method comprising:

selecting as an upper limit a period at which the generator is stopped unless the amount of brake applied to the generator is switched to a first brake setting value,

selecting as a lower limit a period at which the generator vibrates when the amount of brake applied to the generator is switched to the first brake setting value,

P6621a

10/079,658

RESPONSE UNDER 37 CFR §1.312

and setting a first setting period to a period between the upper limit and the lower limit, such that the electronic unit operates to:

compare a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

set the amount of brake applied to the generator to only ~~a~~the first brake setting value when a measured rotation period of the generator is equal to or longer than ~~a~~the first setting period, which is longer than a reference period, to prevent the generator from stopping.

11. (Previously presented) An electronic unit comprising a mechanical energy source, a generator driven by the mechanical energy source to generate induction electric power to supply electrical energy, and a rotation control unit driven by the electrical energy to control the rotation period of the generator, the rotation control unit comprising:

brake control means for comparing a reference signal, generated according to a signal sent from a time reference source, with a rotation detection signal corresponding to the rotation period of the generator to apply brake control to the generator; and

generator-stop preventing means for setting the amount of brake applied to the generator to only a first brake setting value when a measured rotation period of the generator is equal to or longer than a first setting period, which is longer than a reference period, to prevent the generator from stopping.